



DIRECTIONALLY BORING C/C IS A MUCH SAFER & MORE PRODUCTIVE ALTERNATIVE

1. OVERHEAD

- Jacketed Type MC
- MachineFlex™ Tray Cable
- Titan2 Liquid Tight Metal Conduit

2. UNDERGROUND

- SIMPull® Cable in Conduit
- Building Wire (SIMPull® THHN, MTW, AWM, XHHW-2, RHH/RHW-2)
- Bare Copper Grounding
- Aluminum PV Wire 2kV
- Primary MV 5kV-35kV Tape Shield
- Multi Conductor MV Cable

3. EV CHARGING WIRES

- Primary MV 5kV-35kV Concentric Neutral
- USE-2
- MachineFlex™ Power Cable
- DLO
- Multi-Conductor Control Cable
- Titan2 Liquid Tight Metal Conduit
- Data Communication Cable
- Level 2 Charging Cable
- DC Fast Charging Cable
- LC3™ Liquid Cooled Charging Cable

4. ACCESSORIES

- TRIGGERS® Wireless Safety Switch System
- SIMPull® Reel
- QWIKrope® Feeder Pulling Rope
- Temporary Power Boxes
- Maxis® 6K Cable Puller with Motor
- Maxis® XD1 Extreme Duty Circuit Puller